

**Klick&Show**

# Transmitter

**Complete your Klick&Show system with the matching Klick&Show WiFi transmitters to include more participants in the meeting and to increase device compatibility. 4 types of Klick&Show transmitters are available to choose from: either for 4K or 1080P transmission quality, each with HDMI or USB-C type connection.**

#### **4K Transmitter Highlights:**

- > High-resolution 4K transmission with low latency
- > Multi-color LED indicator
- > Show button + 2 auxiliary buttons for triggering additional functions
- > Mirror your primary or secondary desktop
- > Connection: HDMI (plus USB-A for power + Touchback)
- > Connection: USB-C (requires support for Display-Port alternate mode)

#### **Full-HD Transmitter Highlights:**

- > Full-HD transmission with low latency
- > Dual-color LED indicator
- > Sensor button + vibration status feedback
- > Mirror your primary or secondary desktop
- > Connection: HDMI (plus USB-A for power + Touchback)
- > Connection: USB-C (requires support for Display-Port alternate mode)

Klick&Show HDMI and USB-C transmitters are truly plug & play devices and facilitate completely software and driver-free content mirroring. It's as easy to use as connecting an external PC monitor: plug the transmitter into the video port of your computer or compatible HDMI or USB-C device and click the show button to wirelessly share live content to the main screen. All transmitter types allow mirroring of either primary or extended desktop.

With its built-in WiFi module, the transmitters automatically connect to the Klick&Show base unit. A simple "Klick" on the transmitter's show button starts or stops the streaming.

Outstanding performance is guaranteed thanks to the hardware-accelerated transmission technology. An integrated chip delivers ultra-low latency streaming, so your content is mirrored wirelessly to the main display in brilliant quality with up to 4K resolution, without using up your laptop's processing power.

The Klick&Show 4K transmitters let content be mirrored in particularly high resolution. The appealing design features a multi-color LED status display and, alongside the show button, 2 auxiliary buttons for triggering additional functions. While a Klick on the transmitter's Show button starts and stops the streaming, the auxiliary buttons allow for example the transmission to be temporarily paused or to switch from split screen mode into full screen view. Combined with the top-of-the-range K-FX Plus model, further function definitions can even be customized, for example to trigger the Dual-Cam function, the Dual-UCC function or the HDMI input. What's more, K-FX Plus lets you receive a mirrored live view of the entire main display for sharing collaborative local content with remote participants in a BYOM call.

Connected to Windows or MacOS computers, all transmitters support the "touchback" function, allowing the computer to be operated remotely via an interactive display at the base unit. Keep your meeting table organized with the optional TRAY-4K in the matching design.

# Details



## Technical specifications

Connector
Compatible base unit
Integrated CD-ROM memory for apps and drivers
USB standard
Input resolutions
Video standard
Audio
USB HID function
Frame rate
Output resolution
Latency
WiFi frequency band
WiFi standard
WiFi antennas
WiFi bandwidth
WiFi range
WiFi security standard
Housing / color
Operation
Auxiliary buttons, function assignment
LED
Dimensions (W x D x H)
Connection cable (length)
Weight
Power consumption
Power supply
Part number

## 4K HDMI Transmitter

HDMI, USB-A
Klick&Show K-40/K-42, K-FX & K-FX Plus
Yes, when paired with K-FX series base unit. No CD-ROM memory when paired with K-40 series base unit.
2.0
up to 3840x2160p@30Hz
HDMI 1.4, HDCP 1.4
2CH PCM
yes
60 fps (max.)
3840x2160p (max.)
< 80 ms
2.4 / 5 GHz
WiFi 6 (IEEE 802.11b/g/n/ac/ax)
MIMO 2x2
up to 866 Mbps
typical: 35 m with unobstructed line-of-sight between transmitter and base unit
WPA PSK, WPA2 PSK, WPA3 PSK
plastic / black
1x tactile main button, 2x tactile auxiliary button
2x, customizable for K-FX Plus, fixed for K-FX/K-40
multi-color LED status display
77 x 77 x 18 mm
approx. HDMI 11 cm, approx. USB 20 cm
approx. 100 g
approx. 2.5 W
via USB 5V
7488 000 364

## 4K USB-C Transmitter

USB-C
Klick&Show K-40/K-42, K-FX & K-FX Plus
Yes, when paired with K-FX series base unit. No CD-ROM memory when paired with K-40 series base unit.
2.0
up to 3840x2160p@30Hz
DP 1.2, eDP 1.4, HDCP 1.3
2CH PCM
yes
60 fps (max.)
3840x2160p (max.)
< 80 ms
2.4 / 5 GHz
WiFi 6 (IEEE 802.11b/g/n/ac/ax)
MIMO 2x2
up to 866 Mbps
typical: 35 m with unobstructed line-of-sight between transmitter and base unit
WPA PSK, WPA2 PSK, WPA3 PSK
plastic / black
1x tactile main button, 2x tactile auxiliary button
2x, customizable for K-FX Plus, fixed for K-FX/K-40
multi-color LED status display
77 x 77 x 18 mm
approx. 11 cm
approx. 90 g
approx. 2.5 W
via USB 5V
7488 000 365

## HDMI Transmitter

HDMI, USB-A
Klick&Show K-40/K-42, K-FX & K-FX Plus
Yes, when paired with K-FX series base unit.
2.0
up to 2540x1440p@60Hz
HDMI 1.4, HDCP 1.4
2CH PCM
yes
60 fps (max.)
1080p (max.)
< 100 ms
2.4 / 5 GHz
WiFi 5 (IEEE 802.11b/g/n/ac)
MIMO 2x2
up to 866 Mbps
typical: 35 m with unobstructed line-of-sight between transmitter and base unit
WPA PSK, WPA2 PSK
plastic / black
sensor button with vibration feedback
-
sensor button with vibration feedback
80 x 60 x 15 mm
approx. HDMI 11 cm, approx. USB 20 cm
approx. 100 g
approx. 2.5 W
via USB 5V
7488 000 344

## USB-C Transmitter

USB-C
Klick&Show K-40/K-42, K-FX & K-FX Plus
Yes, when paired with K-FX series base unit.
2.0
up to 2540x1440p@60Hz
DP 1.2, eDP 1.4, HDCP 1.3
2CH PCM
yes
60 fps (max.)
1080p (max.)
< 100 ms
2.4 / 5 GHz
WiFi 5 (IEEE 802.11b/g/n/ac)
MIMO 2x2
up to 866 Mbps
typical: 35 m with unobstructed line-of-sight between transmitter and base unit
WPA PSK, WPA2 PSK
plastic / black
sensor button with vibration feedback
-
sensor button with vibration feedback
80 x 60 x 15 mm
approx. 11 cm
approx. 90 g
approx. 2.5 W
via USB 5V
7488 000 345



More informations  
Visit our website for  
more information

Subject to change in the interest of progress. Illustrations and technical specifications may contain additional options and are not binding for the design. All dimensions are subject to the usual tolerances.

proudly presented by:



Kindermann GmbH  
Mainparkring 3 | 97246 Eibelstadt | Germany  
Tel. +49 9303 9840-0 | Fax +49 9303 9840-101  
Printed in Germany | 10/24 | 0101009002

www.kindermann.com

